

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-001583

(43)Date of publication of application : 06.01.1998

(51)Int.Cl.

C08L 27/06

C08K 3/22

C08K 5/07

(21)Application number : 08-154025

(71)Applicant : TATSUTA ELECTRIC WIRE &
CABLE CO LTD
KOSEI:KK
NITTO KASEI KOGYO KK

(22)Date of filing : 14.06.1996

(72)Inventor : FUJIO NOBUHIRO
MURAKAMI KEIICHI
HIRAMATSU TSUNENOSUKE
MIHARA JUNICHI
IWASE TORU

(54) FLAME-RETARDANT HALOGENATED RESIN COMPOSITION FOR TRANSPARENT MOLDING

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain excellent flame retardancy by blending a halogenated resin with an Sb₂O₅ powder having a mean particle diameter below a specified value and a β -diketone compound or a metal salt thereof.

SOLUTION: A halogenated resin such as a vinyl chloride resin in an amount of 100 pts.wt. is blended with 1.0-10 pts.wt. Sb₂O₅ powder having a mean particle diameter of at most 30 μ m and 0.01-5 pts.wt. β -diketone compound or zinc salt thereof, such as dibenzoylmethane or zinc salt thereof. If necessary, this mixture is blended with a plasticizer such as tricresyl phosphate, a Ba-Zn composite stabilizer, an antioxidant, an antistatic agent, an anti-fogging agent, etc., each in a specified amount, and the blend is kneaded with, e.g. a hot roll to give a flame-retardant halogenated resin composition.

LEGAL STATUS

[Date of request for examination]